

DIRECTIONS FOR USE



TECTALOY PLUS - MUKOWT RADIATOR FLUSH

Product Code	Size	Colour
TE610	500ml	-

DIRECTIONS FOR USE:

1. Drain cooling system of all coolant
2. Refill with clean soft or demineralised water
3. Add 500ml of Mukowt for every 10 litres of water
4. Run engine for minimum of 20 minutes. For extremely dirty cooling systems increase running time to several hours and repeat flushing procedure until clean
5. Flush out cooling system with clean, soft or demineralised water
6. Fill with the correct Tectaloy coolant to suit your vehicle

TECTALOY PLUS RADIATOR STOP LEAK

Product Code	Size	Colour
TESL500	500ml	-

DIRECTIONS FOR USE:

1. Shake bottle and carefully add contents to radiator
2. Run vehicle for 15 minutes to ensure full circulation
3. Check leak has sealed and top up coolant if necessary
4. Replace faulty or leaking component as soon as possible
5. If spilled on paintwork wash off with water immediately
6. Used coolants may harm the environment. Dispose of as directed by the EPA. Store in a sealed container out of direct sunlight.

TECTALOY PLUS RADIATOR STOP LEAK

Product Code	Size	Colour
TEHD21L	1L	-

DIRECTIONS FOR USE:

1. Drain cooling system of old coolant. Seal cooling system and add HD2 Heavy Duty Radiator Flush
2. Refill system with clean, soft or demineralised water
3. Open heater circuit and run engine at a fast idle for 15 minutes. A maximum run time of two hours should not be exceeded
4. When cool, drain the cooling system and flush thoroughly with clean, soft or demineralised water, repeat until clean
5. The cooling system is now ready for an addition of a suitable Tectaloy Coolant