

## TECTALOY RADIATOR STOP LEAK

#### INTRODUCTION

Tectaloy Stop Leak is designed specifically to be compatible with the complete range of Tectaloy coolants and inhibitors. It quickly seals leaks in radiators (aluminium, copper/brass), heaters, thermostat housings and water pumps and is effective at controlling gasket seepage. Stop Leak is a temporary repair product and not intended as a permanent fix. The contents will treat a cooling system up to 12 litres capacity.

#### TYPICAL APPLICATIONS

Radiators, heaters, thermostat housings and water pumps

#### **ADVANTAGES**

- · Fast acting formula.
- · Suitable for alumiminium, copper and brass.
- · Stops and prevents leaks.
- · Can be added to existing radiator fluid.
- Enables system to operate until repairs can be made.

#### **SPECIFICATIONS**

- · Ready to use.
- · Compatible with all coolants.
- 500mL treats 12 litre capacity.



FAST ACTING FORMULA

READY TO USE

**SEALS RADIATOR LEAKS** 

#### Turn over for usage directions

Product Code	Size	Product Barcode	Ctn. Qty.	Carton Barcode
TESL500	500mL	9312924005131	6	19312924005138



### **DIRECTIONS FOR USE**

# **TECTALOY PLUS**RADIATOR STOP LEAK

Product Code	Size	Colour
TESL500	500ml	_

#### **DIRECTIONS FOR USE:**

- 1. Shake bottle and carefully add contents to radiator
- 2. Run vehicle for 15 minutes to ensure full circulation
- 3. Check leak has sealed and top up coolant if necessary
- 4. Replace faulty or leaking component as soon as possible
- 5. If spilled on paintwork wash off with water immediately
- 6. Used coolants may harm the environment. Dispose of as directed by the EPA. Store in a sealed container out of direct sunlight.

